

item:  
**coventry**

product profile for upholstery fabrics in living areas  
according to DIN EN 15618:2012-08

roll length:	≈ 30m	width:	142cm ±2cm
useable width:	140cm ±2cm	weight m DIN EN 2286-2:	710gr ±5%
thickness:	1,1mm ±2%	weight m <sup>2</sup> DIN EN 2286-2:	510gr ±5%
composition surface:	92% PVC, 8%polyurethane		
composition base fabric:	100% polyester		
abrasion test (EN ISO 5470-2) method 1:	>62 000 cycles (Martindale)	category A	
tensile strength (EN ISO 1421) method 1:			
warp:	>380 N/5cm	category A	
weft:	>280 N/5cm	category A	
tear growth resistance (EN ISO 4674-1) method B:			
warp:	>50 N	category A	
weft:	>50 N	category A	
fastness to rubbing (EN ISO 105-X12) dry:			
bright colors:	>5	category A	
dark colours:	>5	category A	
fastness to rubbing (EN ISO 105-X12) wet:			
bright colors:	>5	category A	
dark colours:	>5	category A	
fastness to light (EN ISO 105-B02)*			
bright colors:	>5	category A	
dark colours:	>5	category A	
hydrolysis (DIN EN 12280-1 (14d/70°C/ 95-98% rh) / DIN 53359 (15 000 cycles))	lengthwise (warp), across (weft), diagonal		
	passed		
<b>fire protection BS 5852 Part 0; Part I (DIN EN 1021-1,2)</b>	<b>on request</b>		

\*category for indoor use only.

## phthalate free